

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR LETTERS PATENT

Title of the Invention: UVC TRANSPORT CART

Inventor: Thomas Eric Carter

Twenty Claims
Three Sheets of Drawings

Express Mail Label No.: EV 264377501 US
I hereby certify that this correspondence is being deposited with the
United States Postal Service as "Express Mail Post Office to Addressee"
service under 37 CFR 1.10 on the date indicated below, and is
addressed to: Mail Stop Design, Commissioner for Patents, P.O. Box
1450, Alexandria, VA 22313-1450 on

3/24/04

(Date of Deposit)

Pasquale A. Razzano

(Name of Attorney for Applicant)


(Signature)

3/24/04
(Date of Signature)

Pasquale A. Razzano
Registration No. 25,512
30 Rockefeller Plaza
New York, NY 10112-3801
Telephone: (212) 218-2100
Facsimile: (212) 218-2200

TITLE

UVC TRANSPORT CART

5 **BACKGROUND OF THE INVENTION**

Field of the Invention

[0001] The present invention relates to a food service transport cart, more in particular, to a cart utilizing ultraviolet irradiation for disinfecting the interior of
10 the cart each time the doors to the cart are opened.

Background of the Invention

[0002] In hospitals and other institutions, or places of public accommodation which require food prepared in a central location to be transported directly to the
15 patient or guest, various types of transportation carts are used. Typically, these carts have one or two doors and a food tray support system contained therein for holding one or more trays of food to be delivered to one or more individuals or sites within the particular building involved. These carts are designed to hold hot, warm or cold foods in an insulated environment during the typical delivery time
20 period. In some cases the carts are simply reused, without cleansing, and in others,

particularly in health care facilities, the carts may be washed or cleaned between delivery periods. However, they may be used multiple times within a particular delivery period.

[0003] It has been found, particularly within hospitals or buildings of public
5 accommodations or the like, that bacteria or viruses in the air may enter the cart during a particular delivery, and remain in the cart during further deliveries. This results because the surrounding air in the building is allowed to enter the inner holding chamber of the cart. As a result, food, utensils and dishware in the cart to be delivered to subsequent patients may become contaminated with undesirable
10 bacteria and viruses and create an unnecessary health hazard.

[0004] Although it has previously been proposed to provide ultraviolet irradiation in particular food storage stationary facilities, such as, for example, certain refrigeration units or microwave ovens, no system has previously been developed utilizing ultraviolet radiation, a known and successful method of disinfecting
15 spaces in a food service cart so that the items in the cart are continuously disinfected while the cart is in use and its doors repeatedly opened and close.

Objective of the Invention

[0005] It is an object of the present invention to provide an improved food service
20 cart with a self-contained air disinfection system.

[0006] Another object of the invention is to provide an ultraviolet irradiation device for a food service cart which is relatively simply in construction and adapted for use in a portable cart.

[0007] A further object of the present invention is to provide a mobile food service cart self-contained irradiation unit, selectively operable for predetermined periods of time after the door or doors of the cart are opened.

5 **Brief Summary of the Invention**

[0008] In accordance with an aspect of the present invention, a food service transport cart is provided which includes a mobile housing, preferably mounted on wheels, that includes at least one door which provides selective access to the interior of the housing. The housing contains a tray support system, such as, for
10 example, molded support flanges on its side walls and a central wall, which are adapted to support a plurality of food service trays in one or more stacks with the trays spaced from one another to allow room therebetween for the food, utensils and dishware on the tray.

[0009] At least one UV-C irradiation lamp is positioned in the housing, for
15 example, on the interior surface of the front door or on the back wall, in order to expose the air and items in the housing to the disinfection effects of the ultraviolet light.

[0010] A power source is mounted in the housing for selectively supplying electrical power to the light source. This power source consists of a rechargeable
20 battery pack for supplying electrical power or current to the UV-C lamp. One or more switches are positioned in the cart and connected between the power source and the lamp or lamps, to allow power to flow from the battery pack to the lamp when the door is closed. These switches operate on contact with the closed door, and are in turn connected to a timer which will cut off the power supply to the lamp

or lamps after a predetermined period of time following the closure of the door. If the doors are opened before that predetermined period of time passes, the light is automatically shut off when the door moves away from the contact switches. This will automatically reset the timer.

5 [0011] The light sources used in the present invention are shaped similarly to fluorescent tubular light bulbs, but produce ultraviolet light. Such light sources or lamps produce UV-C irradiation at a wavelength of about 254 nm, with an intensity of about 142 $\mu\text{w}/\text{cm}^2$. Preferably, the lights are positioned in a vertical direction and have a length sufficient to cover substantially the entire interior height of the
10 enclosure so that all of the trays and air spaces between them are exposed directly to UV light.

[0012] The disinfection unit of the present invention will be able to disinfect the cabinet air and interior inactivate common bacteria found in hospital and other institutional air, such as escherichia coli, pseudomonas, fluoresces, serratia
15 marcescen, Micrococcus, luteus and bacillus subtilis.

[0013] The battery pack used in the food service carts of the present invention preferably are rechargeable so that each time the cart is put in storage, for example, between service delivery periods, it may be plugged into a wall to recharge the battery.

20 [0014] The above, and other objects, features, and advantages of this invention will be apparent in the following detailed description of illustrative embodiments thereof, which is to be read in connection with the accompanying drawings wherein:

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Fig. 1 is a perspective view of a food service cart constructed in accordance with the present invention;

[0016] Fig. 2 is a sectional view taken along line 2 - 2 of Fig. 1;

5 [0017] Fig. 3 is a sectional view taken along line 3 - 3 of Fig. 2;

[0018] Fig. 4 is a sectional view similar to Fig. 2 of another embodiment of the invention;

[0019] Fig. 5 is a sectional view similar to Fig. 2, with the doors removed, of the embodiment of Fig. 4 showing the interior tray support system and the UV light

10 source mounted on the rear wall of the cart;

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0020] Referring now to drawings in detail, and initially to Fig. 1, a food service transport cart 10, constructed in accordance with the present invention is illustrated.

The cart includes a generally rectangular or other shaped housing 12 of

15 conventional relatively rigid but lightweight construction containing an interior space and an opening 14 in its front wall 16. Preferably, the cart is formed with insulated walls in order to maintain the food placed in the cart for delivery in a relatively warm or cool state.

[0021] The opening 14 is closed by one or more doors 18. In the illustrative

20 embodiment, two doors 18 are utilized which are hinged on opposite sides of opening 14 to the side walls of the housing. The doors also are formed of conventional materials, and may have integral handles 20 for selectively opening one or both sides thereof.

[0022] The cart is supported on dolly type wheels 22 in a conventional manner so that it can be easily moved through the corridors of the hospital or institution.

Preferably, a handle 24 is provided on one of the side walls of the cart for ease of maneuvering by the operator.

- 5 [0023] One form of material that could be used to manufacture the housing and doors of the cart is a stressed skin thermoplastic panel material having a foam filled center for insulation. Such panel structure materials are commercially available and need not be described herein in detail.

- [0024] The interior of the transport cart 12 includes a tray support structure which
10 may be of any conventional form currently used in the food service industry. In the illustrative embodiment of the invention, the inner surfaces 26 of the sidewalls of the cart are formed with integral flanges 28 extending therefrom at predetermined vertically spaced intervals. A central support panel 30 is also provided, which has similar support flanges 28 integrally formed therein at the same levels as the flanges
15 28 on the sidewalls. Thus, these flanges provide support surfaces for food service trays 30, illustrated in dotted lines in Figs. 2 and 3.

[0025] As noted above, in one embodiment of the invention, the UV light sources 32 are mounted on the inner surfaces 34 of the cart door or doors. These UV lights are commercially available in different sizes and need not be described in detail.

- 20 Their external physical appearance is similar to that of tubular fluorescent bulbs, with contact elements at their ends that are supported in electrical contact sockets 36 in a known manner. Such bulbs may also be mounted on the back wall of the cart.

[0026] In the embodiment of the invention illustrated in Fig. 2, the bulbs are mounted on the inner face of the door, and project therefrom. Preferably, in this embodiment the bulbs would be guarded by a protective grid, lens or other transparent barrier (not shown) to avoid inadvertent contact with the trays or other
5 objects which might cause the bulbs to break.

[0027] In the embodiment of the invention illustrated in Fig. 4, recesses 38 are formed in the inner surfaces 34 of the doors, and the bulbs 32 and sockets 36 are mounted within the recess. This structure provides further protection for the bulb against inadvertent breakage. However, if desired any form of convenient
10 transparent lens or shielding system to protect the bulb may also be installed over the recesses.

[0028] While the above illustrative embodiments of the present invention show a single bulb on each door, the number of bulbs to be utilized can vary depending upon the size of the cart.

15 [0029] The embodiment of the invention illustrated in Fig. 4 also shows the use of UV bulbs 32 mounted within recesses 40 formed in the back wall of the housing. As with the other embodiments, the ends of the bulbs are mounted in conventional sockets 36 appropriate for the bulbs. When bulbs are used on the rear wall the bulbs on the door may optionally be omitted.

20 [0030] In accordance with another feature of the present invention, the UV bulbs are provided with power through electrical connectors (not shown) from a rechargeable battery pack 42 of conventional construction. The battery pack is mounted in or on the cart in any convenient manner. In the illustrative embodiment

of the invention shown in Fig. 5, it is mounted on the bottom wall 44 in the center of the cart.

[0031] On/off switches 46 are provided in the bottom of the cart in position to contact the door or doors when they are closed. In the illustrative embodiment of the invention shown in Fig. 4, the switches are depicted as being on the bottom wall 44 of the cart adjacent the battery pack. However, they could be mounted on the top wall or the central support member 30 as well. The switches are set so that when the door is closed the switches allow current to pass from the battery pack to the UV bulbs. When the door is opened, the switches open the circuit so that the bulbs are extinguished in order to avoid undesirable exposure to personnel in the area.

[0032] Because the space within the housing 12 is limited, it is not necessary for the UV bulbs to be operating at all times. Thus, a timer 48 is provided in conjunction with switches 46 so that after the switches have allowed the UV lamps to operate for a predetermined period of time sufficient to disinfect the interior of the cart, current to the lamps is shut off. This not only preserves the life of the battery pack, but avoids unnecessary exposure of the interior of the cart to the UV light waves. In addition, the timer is selected such that if the doors are opened before the lights have been on for the desired period of time, not only will the switches cause the lights to be shut off, but the timer will reset itself for a new complete timing period to commence once the doors are again closed.

[0033] While the UV lamps have been shown on the doors or rear of the interior of the enclosure, they may be located elsewhere within the transport cart as would occur to those skilled in the art. For example, individual horizontal bulbs could be

mounted in the recesses in the side walls of the cart between the flanges or support elements 28. Such an arrangement, like the vertical arrangement described above in the illustrated embodiments, assures that all exposed surfaces and all of the air on the interior of the cart are exposed to the UV light each time the doors are opened
5 and closed.

[0034] Although illustrative embodiments of the present invention have been described herein in detail, it is to be understood that the invention is not limited to those precise embodiments, and that various changes and modifications can be affected therein without departing from the scope or spirit of this invention.